



# auxiliary contact, Acti9, iOF, 1 OC, AC/DC

A9A26924

! Discontinued on: 01-Jun-2024



#### Main

range of product	Acti9	
Product or component type	OC contact	
Device short name	iOF	
Signal contacts composition	1 C/O	
[In] rated current	AC-12 6 A at 240 V, AC 50/60 Hz	
	AC-12 3 A at 415 V, AC 50/60 Hz	
	DC-12 2 A at 48 V, DC	
	DC-12 1.5 A at 60 V, DC	
	DC-12 1 A at 130 V, DC	
	DC-12 6 A at 24 V, DC	
9 mm nitches	1	

mm pitches

## Complementary

[Ui] rated insulation voltage	500 V	
[Uimp] rated impulse withstand voltage	4 kV	
mounting mode	Clip-on	
mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top: YES	
Height	86 mm	
Width	9 mm	
Depth	73 mm	
Net weight	32 g	
Colour	White	
Connections - terminals	Screw clamp terminal (bottom) 1 cable(s) 14 mm² - rigid Screw clamp terminal (bottom) 1 cable(s) 0.52.5 mm² - flexible Screw clamp terminal (bottom) 2 cable(s) 2.5 mm² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible with ferrule	
Wire stripping length	10 mm	
Tightening torque	1 N.m	

## **Environment**

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1

Tropicalisation	2 conforming to EN/IEC 60947-5-1	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for	-4085 °C	

## **Packing Units**

r adming dimes		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.800 cm	
Package 1 Width	2.000 cm	
Package 1 Length	9.200 cm	
Package 1 Weight	40.000 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	12	
Package 2 Height	8.500 cm	
Package 2 Width	10.000 cm	
Package 2 Length	27.200 cm	
Package 2 Weight	570.000 g	
Unit Type of Package 3	S03	
Number of Units in Package 3	120	
Package 3 Height	30.000 cm	
Package 3 Width	30.000 cm	
Package 3 Length	40.000 cm	
Package 3 Weight	6.350 kg	

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>9</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information