

# Product data sheet

Specifications



## TeSys Deca control relay - 3 NO + 2 NC - ≤ 690 V - 110 V AC standard coil

CAD32F7

Product availability: Stock - Normally stocked in distribution facility

Price\*: 63.25 USD

### Main

Range	TeSys TeSys Deca
Product name	TeSys CAD
Product or Component Type	Control relay
Device short name	CAD
Contactors application	Control circuit

### Complementary

Utilisation category	AC-15 AC-14 DC-13
Pole contact composition	3 NO + 2 NC
[Ue] rated operational voltage	≤ 690 V AC 25...400 Hz
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	110 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C))
Irms rated making capacity	140 A AC IEC 60947-5-1 250 A DC IEC 60947-5-1
[Icw] rated short-time withstand current	100 A - 1 s 120 A - 500 ms 140 A - 100 ms
Associated fuse rating	10 A gG conforming to IEC 60947-5-1
[Ui] rated insulation voltage	600 V UL 600 V CSA 690 V IEC 60947-5-1
Mounting Support	Rail Plate
Connections - terminals	screw clamp terminals 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end screw clamp terminals 2 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end screw clamp terminals 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end screw clamp terminals 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end screw clamp terminals 2 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end
Tightening torque	10.6 lbf.in (1.2 N.m) screw clamp terminals Philips No 2 10.6 lbf.in (1.2 N.m) screw clamp terminals flat Ø 6 mm 10.6 lbf.in (1.2 N.m) screw clamp terminals pozidriv No 2

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Control circuit voltage limits</b>	0.3...0.6 Uc -40...158 °F (-40...70 °C) drop-out AC 50/60 Hz 0.8...1.1 Uc -40...140 °F (-40...60 °C) operational AC 50 Hz 0.85...1.1 Uc -40...140 °F (-40...60 °C) operational AC 60 Hz 1...1.1 Uc 140...158 °F (60...70 °C) operational AC 50/60 Hz
<b>Operating time</b>	12...22 ms coil energisation and NO closing 4...12 ms coil de-energisation and NO opening 4...19 ms coil energisation and NC opening 6...17 ms coil de-energisation and NC closing
<b>Mechanical durability</b>	30 Mcycles
<b>Maximum operating rate</b>	180 cyc/mn
<b>Inrush power in VA</b>	70 VA 50 Hz (at 68 °F (20 °C))
<b>Hold-in power consumption in VA</b>	8 VA 50 Hz (at 68 °F (20 °C))
<b>Minimum switching voltage</b>	17 V
<b>Minimum switching current</b>	5 mA
<b>Non-overlap time</b>	1.5 ms on energisation between NC and NO contact 1.5 ms on de-energisation between NC and NO contact
<b>Insulation resistance</b>	> 10 MOhm
<b>Mechanical robustness</b>	Shocks control relay open10 Gn for 11 ms IEC 60068-2-27 Shocks control relay closed15 Gn for 11 ms IEC 60068-2-27 Vibrations control relay open2 Gn, 5...300 Hz IEC 60068-2-6 Vibrations control relay closed4 Gn, 5...300 Hz IEC 60068-2-6
<b>Height</b>	3.03 in (77 mm)
<b>Width</b>	1.8 in (45 mm)
<b>Depth</b>	3.3 in (84 mm)
<b>Net Weight</b>	1.28 lb(US) (0.58 kg)

## Environment

<b>Standards</b>	EN/IEC 60947-5-1 GB/T 14048.5 UL 60947-5-1 CSA C22.2 No 60947-5-1 JIS C8201-5-1
<b>Product Certifications</b>	CB CCC UL CSA EAC CE UKCA
<b>IP degree of protection</b>	IP2X front face VDE 0106
<b>Protective treatment</b>	TH IEC 60068
<b>Ambient air temperature for operation</b>	-40...140 °F (-40...60 °C) 140...158 °F (60...70 °C) with derating
<b>Ambient Air Temperature for Storage</b>	-76...176 °F (-60...80 °C)
<b>Operating altitude</b>	0...9842.52 ft (0...3000 m)

## Ordering and shipping details

<b>Category</b>	US10I1222371
<b>Discount Schedule</b>	0112
<b>GTIN</b>	3389110534276
<b>Returnability</b>	Yes

---

Country of origin	FR
-------------------	----

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	2.2 in (5.5 cm)
------------------	-----------------

---

Package 1 Width	3.7 in (9.5 cm)
-----------------	-----------------

---

Package 1 Length	4.5 in (11.4 cm)
------------------	------------------

---

Package 1 Weight	12.5 oz (353 g)
------------------	-----------------

---

Unit Type of Package 2	S02
------------------------	-----

---

Number of Units in Package 2	20
------------------------------	----

---

Package 2 Height	5.9 in (15 cm)
------------------	----------------

---

Package 2 Width	11.8 in (30 cm)
-----------------	-----------------

---

Package 2 Length	15.7 in (40 cm)
------------------	-----------------

---

Package 2 Weight	16.700 lb(US) (7.575 kg)
------------------	--------------------------

---

Unit Type of Package 3	P06
------------------------	-----

---

Number of Units in Package 3	320
------------------------------	-----

---

Package 3 Height	31.5 in (80 cm)
------------------	-----------------

---

Package 3 Width	31.5 in (80 cm)
-----------------	-----------------

---

Package 3 Length	23.6 in (60 cm)
------------------	-----------------

---

Package 3 Weight	282.4 lb(US) (128.1 kg)
------------------	-------------------------

## Contractual warranty

---

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 "WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)"

Image of product / Alternate images

Alternative

---



