
# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





LX1FF110

Discontinued on: 01 Nov 2020

### ① Discontinued

### Main

Panes	T.O.:	
Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1FF	
Range compatibility	TeSys TeSys F LC1F contactor	
Product compatibility	LC1F115 LC1F150	
Control circuit type	AC at 50 Hz	
[Uc] control circuit voltage	110115 V AC 50 Hz	
Inductance of closed circuit	0.86 H	
Average resistance	6.38 Ohm at 20 °C	
Operating time	2335 ms closing 515 ms opening	
Mechanical durability	10 Mcycles	
Maximum operating rate	2400 cyc/h 55 °C	

# Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.350.55 Uc 50/60 Hz (at 55 °C) Operational: 0.851.1 Uc 50/60 Hz (at 55 °C)	
Inrush power in VA	550 VA 50 Hz cos phi 0.3 (at 20 °C)	
Hold-in power consumption in VA	VA 45 VA 50 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	ipation 1216 W at 50 Hz	

### **Environment**

Ambient air temperature for operation	-555 °C	
Net weight	0.43 kg	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.7 cm
Package 1 Width	8.2 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Package 1 Length	gth 16.2 cm	
Package 1 Weight	513 a	

# **Contractual warranty**

Warranty 18 months

# Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

# Well-being performance

Read	ch Free Of Svhc	
<b>O</b> Toxio	: Heavy Metal Free	
✓ Merc	ury Free	
Rohs	Exemption Information	Yes
Eu Rohs D	Directive	Pro-active compliance (Product out of EU RoHS legal scope)
		EU RoHS Declaration
China Roh	ns Regulation	China RoHS declaration