

Product data sheet

Specifications



TeSys F - contactor coil - LX1FL - 110...120 V AC 40...400 Hz

LX1FL110

Product availability: Stock - Normally stocked in distribution facility

Price*: 477.60 USD

Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LX1FL
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F1250 LC1F630
Control circuit type	AC 40...400 Hz
[Uc] control circuit voltage	110...120 V AC 40...400 Hz
Inductance of closed circuit	1.85 H
Average resistance	6.45 Ohm inrush 68 °F (20 °C) 165 Ohm holding 68 °F (20 °C)
Operating time	100...200 ms opening 40...80 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	1200 cyc/h 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 40...400 Hz 131 °F (55 °C) Drop-out 0.25...0.5 Uc 40...400 Hz 131 °F (55 °C)
Inrush power in VA	1650 VA 40...400 Hz cos phi 0.9 (at 68 °F (20 °C))
Hold-in power consumption in VA	22 VA 40...400 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	20 W 40...400 Hz

Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	3.3 lb(US) (1.5 kg)

Ordering and shipping details

Category	US10I1222341
Discount Schedule	0I12
GTIN	3389110082401
Returnability	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	CZ
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	3.9 in (10.0 cm)
------------------	------------------

Package 1 Width	4.7 in (12.0 cm)
-----------------	------------------

Package 1 Length	8.9 in (22.5 cm)
------------------	------------------

Package 1 Weight	3.232 lb(US) (1.466 kg)
------------------	-------------------------

Unit Type of Package 2	S03
------------------------	-----

Number of Units in Package 2	6
------------------------------	---

Package 2 Height	11.8 in (30.0 cm)
------------------	-------------------

Package 2 Width	11.8 in (30.0 cm)
-----------------	-------------------

Package 2 Length	15.7 in (40.0 cm)
------------------	-------------------

Package 2 Weight	20.30 lb(US) (9.21 kg)
------------------	------------------------

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
