

XURC3PPML2

Photoelectric sensors XU, XUR, diffuse, color,
Sn 60 mm, 12...24 VDC, cable 2 m

Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application packaging
Electronic sensor type	Photo-electric sensor
Product specific application	Colour
Sensor name	XUR
Sensor design	Compact
Detection system	Diffuse
Emission	Red, blue and green
[Sn] nominal sensing distance	40 Mm spot Ø 4 mm 50 Mm spot Ø 6 mm 60 mm spot Ø 8 mm
Material	Metal
Supply circuit type	DC
Type of output signal	Discrete
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NO
Electrical connection	Cable
Cable length	2 m

Complementary

Enclosure material	Aluminium
Lens material	Glass
Cover material	Polyacrylate
Output type	Solid state
Output function governance	Light on
Add on input	Synchro + recording
Cable composition	7 x 0.2 mm ²
Wire insulation material	Vinyl rubber
Cable outer diameter	5.4 mm
Status LED	Output state: 3 LEDs
[Us] rated supply voltage	12...24 V DC
Supply voltage limits	10...30 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 1200 Hz
Switching time	6 ms programmable by switch 0.8 ms programmable by switch 1.5 ms programmable by switch
Maximum voltage drop	<1.5 V (closed state)
Current consumption	<= 150 mA no-load
Time delay range	40 ms on failing edge programmable by switch delay
Setting-up	Tolerance level Operating mode Sensitivity adjustment with teach mode
Depth	57 mm
Height	87 mm
Width	30 mm
Product weight	0.26 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE
Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-30...70 °C
Relative humidity	35...85 % without condensation
Immunity to ambient light	10000 Lux sunlight 3000 lux halogen light
Vibration resistance	7 gn, amplitude = +/- 0.75 mm (f = 10...55 Hz) on the 3 axes during 2 hours conforming to IEC 60068-2-6
Shock resistance	50 gn for 5 shocks on each axis conforming to IEC 60068-2-27
IP degree of protection	IP67 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	7.8 cm
Package 1 Length	13.3 cm
Package 1 Weight	290.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.352 kg

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
Take-back	No
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------